



Harris Products Group
Since 1905

Revised on 10/02/2022

Safety Data Sheet

1 IDENTIFICATION

Product identifier

Trade name: **1620 Anti-spatter**

Other means of identification: Methylene Chlorine

SDS Number: 02

Recommended use and restriction on use

Recommended use: Protection against weld spatter

Manufacturer/Importer/Supplier/Distributor information

Importer:

Harris Products Group

14 Queensland Rd

Darra, QLD, Australia 4076

(07) 33753670

Website: <http://www.harrisproductsgroup.com.au>

Safety Data Sheet Questions: sales@hgea.com.au

Poisons Information Centre/Helpline (24 hours) Australia 13 11 26

2 HAZARD(S) IDENTIFICATION

GHS classification of the substance/mixture.

Classified according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

HARMFUL BY INHALATION AND IF SWALLOWED. DANGER OF CUMULATIVE EFFECTS

Classification of the substance or mixture

Eye Irritation Category 2A

Skin Irritation Category 2

Specific Target Organ

Toxicity – Single Exposure Category 3

Carcinogen Category 2

Label Elements: **WARNING! Contains methylene chloride**

GHS label elements



Signal Word

WARNING! Contains methylene chloride

Precautionary Statement

H315 Causes skin irritation

H319 Causes serious eye irritation

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H351 Suspected of causing cancer

Prevention

P201 Obtain special instructions before use

P261 Avoid breath in dust, gas, mist, fumes, vapours, sprays

| | |
|-------------|---|
| P264 | Wash thoroughly after handling |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves, protective clothing, eye protection & face protection |

Response

| | |
|-------------------------|---|
| P305, P351 | IF IN EYES rinse cautiously with water for several minutes. |
| P338 | Continue rinsing |
| P337, P313, P302 | IF EYE IRRITATION PERSISTS Get medical advice and attention |
| P352 | IF ON SKIN Wash with plenty of soap and water |
| P332, P313 | IF SKIN IRRITATION OCCURS get medical advice and attention |
| P362 | Take of contaminated clothing and wash before reuse |
| P304, P340 | IF INHALED Remove to fresh air and rest in a position comfortable for breathing |
| P312 | Call the poison centre or doctor if feeling unwell |
| P308, P403 | IF CONCERNED ABOUT EXPOSURE seek medical advice and attention |

Storage

| | |
|-------------|---|
| P403 | Store in a well ventilated place. Keep container tightly closed |
| P405 | Lock up storage |

Disposal

| | |
|-------------|--|
| P501 | Dispose in accordance with local authority regulations |
|-------------|--|

Additional information:**Other hazards which do not result in GHS classification:**

Not applicable

Results of PBT and vPvB assessment

Not applicable

3 Composition/information on ingredients**Chemical characterization: Mixtures**

Description: Mixture: consisting of the following components.

| Dangerous components: | | |
|------------------------------|--------------------|-------------------|
| CAS | Name | Proportion |
| 75-09-2 | Methylene Chloride | 73 - 84% |
| 124-38-9 | Carbone Dioxide | 17% |

Composition comments:

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4 First Aid Measures**Skin Exposure**

Remove with soap and water. Continue flushing with water for several minutes. Use skin cream to counter resulting dryness. Consult a physician if Get medical attention if irritation develops or persists.

Eye Exposure

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Get medical attention if any discomfort continues.

Ingestion

Unlikely due to being in aerosol form. **Do not induce vomiting.** If vomiting occurs, keep head low so that stomach content does not get into the lungs. Never give anything by mouth to an unconscious person. **Get medical attention.**

Medical conditions aggravated from exposure

Acute excessive inhalation and ingestion may produce symptoms of light headedness to unconsciousness to death. Exposure of skin and eye may produce irritation. Chronic headache, fatigue, nausea, depression and visual disturbance. High levels may cause cardiac arrhythmias. Excessive exposure may cause irritation to upper respiratory tract. Excessive exposure may also cause carboxyhemoglobinemia

Recommendations to physicians

Treat symptoms and eliminate overexposure. Call for medical aid. Employ first aid techniques recommended by the Australian Red Cross

5 Fire-fighting measures

Material may burn but not ignite readily.

Extinguishing media:**Suitable extinguishing equipment:**

Dry chemical, foam, carbon dioxide.

Unsuitable extinguishing equipment:

Water or foam (may cause frothing).

Special hazards arising from the product

Heated containers may rupture, explode or be thrown into the air. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

Special protective equipment and precautions for fire fighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Wear suitable protective equipment.

Fire fighting equipment/instructions:

Containers close to fire should be removed or cooled with water.

Hazardous combustion products:

Product may decompose upon heating to produce phosgene, halogenated compounds, carbon monoxide, and unidentified organic compounds.

Additional information

Read and understand the Work Safe Australia Code of Practice on Welding Processes and "Standard for Fire Prevention During Welding, Cutting and Other Hot Work" before using this product. Section 274 of the Work Health and Safety Act (the WHS Act.)

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Avoid prolonged or repeated skin contact. Avoid breathing vapours. Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapours have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal considerations.

Environmental precautions

Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content should be contained as any other solvent spill. Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapours and ventilate area well. Remove all sources of ignition and use non-sparking equipment. Soak up material with inert absorbent. Flush area with water. All rinsate should be placed in safety containers and labelled for proper disposal.

Methods and materials for containment and cleaning up.

Collect for salvage or disposal. Collect any released materials with absorbent, non-combustible material into suitable containers. Clean surface thoroughly to remove residual contamination. Should not be released into the environment.

7 Handling and storage

Handling:

Precautions for safe handling

Avoid inhalation of vapours/spray and contact with skin and eyes. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment (See Section 8). Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed and in a well-ventilated place. Keep away from incompatible material. Keep away from food, drink and animal feeding stuffs. Heat, sparks, open flame, red hot metal, electrical arcs, high pressure in aluminium systems.

8 Exposure controls/personal protection

Exposure controls

| Source | CAS # | Material | TWA mg/m ³ | TWA (ppm) | STEL mg/m ³ | STEL (ppm) |
|------------------------------|----------|--------------------|-----------------------|-----------|------------------------|------------|
| Australia Exposure Standards | 124-38-9 | Carbon Dioxide | 9000 | 5000 | 54000 | 34000 |
| Australia Exposure Standards | 75-09-2 | Methylene Chloride | 174 | 50 | | |

Engineering Controls

Provide adequate ventilation and minimize the risk of inhalation of vapours and mists. Local exhaust is recommended. Shower, hand and eye washing facilities near the workplace are recommended.

Personal protective equipment:

Respiratory Measures

None during normal use

Ventilation

Local exhaust -sufficient to maintain tlv.

Breathing equipment:

Use appropriate engineering control such as process enclosures, local exhaust ventilation to control Airborne levels below recommended exposure limits.

When ventilation is not sufficient to remove airborne levels from the breathing zone, a NIOSH safety approved respirator or Self-contained breathing apparatus should be worn. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Protection of hands:



Polyfluorinated polyethylene suggested

Suitable gloves can be recommended by the glove supplier.

Eye protection:



Face shield and goggles should be worn

Body protection:

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Limitation and supervision of exposure into the environment: No special requirements.

Risk management measures: DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. For maximum safety: be certified for, and wear a respirator at all times when welding or brazing.

9 Physical and chemical properties**Information on basic physical and chemical properties****General Information**

Appearance: Clear colourless liquid

Physical State: Liquid

Colour: Colourless

Odour: Characteristic odour/Chloroform like odour

| | | | |
|--|----------------------|-------------------------------|--------------------------|
| Odour | Characteristic Odour | Flammability | Not Determined |
| Odour Threshold | Not Available | Flash Point | Not Available |
| pH | Not Available | Auto Igniting | Not Available |
| Melting point/range | 183 C° – 185 C° | Solubility water | Soluble in water |
| Vapour Pressure | 390mm Hg | Flash Point | Non Combustible |
| Vapour Density | 1.9 (Air = 1) | Density at 20°C (68°F) | 8.25 |
| Boiling Point & boiling range | 40° at 100kPa | Evaporation Rate | 14.5 (Butyl acetate = 1) |
| Melting Point | Not Applicable | | |

10 Stability and reactivity

Reactivity: Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

Chemical stability: Stable under normal temperatures and pressures.

Conditions to avoid: Avoid exposing aerosol containers to high temperatures, heat, sparks, open flames, red hot metal, electrical arcs or direct sunlight.

Incompatible materials: Acids, alkalis, oxidizing agents, reactive halogens, or reactive metals.

Hazardous decomposition products:

CO, CO₂, phosgene and or HCl.

11 Toxicological information**Acute Toxicity****CHRONIC HEALTH EFFECTS****Acute toxicity:**

May be harmful if swallowed. Exposure to high concentrations of vapour or mist may result in CNS effects such as headaches, nausea and narcosis.

Local effects to skin & eyes:

Components of the product may be absorbed into the body through the skin. Causes skin and eye irritation.

Chronic effects:

Prolonged or repeated exposure may cause toxic effects to the central nervous system. Repeated or prolonged exposure to high concentrations may cause kidney and liver damage.

Carcinogenic categories:

Suspect cancer hazard - may cause cancer.

MIXTURE OF CHEMICALS

| CHEMICAL | TOXICITY LEVELS | IRRITATION |
|--------------------|--|---------------|
| Methylene Chloride | Carcinogenicity Category 2A – For Humans. May cause cancer | |
| Methylene Chloride | Carcinogenicity Category 3 – For Animals Inhalation (rat) LC50: 50, 100 mg/m ³ /8 hrs Oral rat LD50: 1600 mg/kg | |
| Carbon Dioxide | Inhalation (mouse) LC50: 100000 ppm/2hr ^[2] | Not Available |
| Carbon Dioxide | Inhalation (rat) LC50: 58750 ppm/30M ^[2] | |

12 Ecological information**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

| Ingredient | Result | Species | Exposure |
|--------------------|---------------|-------------------------|-----------|
| Methylene Chloride | LC50 8300 ppm | Fish | 96 hours |
| | LC50 10 ppm | Daphnia Magna | 48 hours |
| Carbon Dioxide | 53.413 mg/L | Fish | 96 hours |
| | 237.138 mg/L | Algae or aquatic plants | 96 hours |
| | 12.472 mg/L | Crustacea | 384 hours |

For carbon dioxide:

Environmental Fate: Carbon dioxide in earth's atmosphere is considered a trace gas. There are seasonal fluctuations of atmospheric concentrations of carbon dioxide primarily due to CO₂ absorbed during seasonal plant growth. Due to human activities such as the combustion of fossil fuels and deforestation, the concentration of atmospheric carbon dioxide has increased by about 35% since preindustrial times. Carbon dissolved in the oceans is about 50 times greater than CO₂ found in the atmosphere.

Persistence and degradability:

Low in Water/ Soil Low in Air

Bioaccumulative Potential:

Low (logKOW = 0.83)

Mobility in Soil:

High (KOC = 1.498)

For Methylene Chloride**Persistence and degradability:**

Product is volatile and biodegradable

Mobility:

Because of its volatility this product is not regarded as creating longer term ecological risks.

PBT and vPvB assessment Not applicable

Other adverse effects

No data available.

13 Disposal considerations**Waste treatment methods****Recommendation:**

An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be

recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state/provincial regulations. Collected rinsate materials from spills may be hazardous wastes, and therefore subject to local, state/provincial and federal regulations. **Uncleaned packagings:**

Recommendation: Disposal must be made according to official regulations.

14 Transport Information

| | |
|--|-------------------------|
| Labels Required | |
| Marine Pollutant | NO |
| HAZCHEM | Not Applicable |
| UN-Number – DOT, ADR, ADN, IMDG, IATA | UN 1950 |
| UN proper shipping name DOT, ADR, ADN, IMDG, IATA | AEROSOLS |
| Transport hazard class(es) DOT, ADR, ADN, IMDG, IATA | 2.2 (Non-flammable Gas) |
| Subsidiary hazard Class | 6.1 |
| Packing Exceptions DOT, ADR, IMDG, IATA | 306 |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

15 Regulatory information

Product Name: 1620 Anti Spatter

Label for supply:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Risk Phrases: R-20/22 Harmful by inhalation and if swallowed.
R-33 Danger of cumulative effects
S-20 When using do not eat or drink

Safety Phrases: S-13 Keep away from food, drink and animal feeding stuffs
S-23 Do not breathe gas/fumes/vapour/spray

Refer to the Australian Inventory of Chemical Substances – AICS at <https://www.nicnas.gov.au/chemicals-on-AICS#main>

Poison schedule: Classified as a Schedule 6 (S6) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). <https://www.legislation.gov.au/Details/F2016L01638>

Classifications: Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

16 Other information

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice

Standard for the Uniform Scheduling of Medicines and Poisons

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Modell Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work, Australia

American Conference of Industrial Hygienists (ACGIH)

Globally Harmonised System of classification and labelling of chemicals.

WELDING (1): Due to the diversity of welding techniques, processes, materials used, nature of the surface being welded and the presence of contaminants, the fumes & gases associated with welding will vary in composition and quantity. When assessing a welding process, the toxic fumes generated may not only be associated with the parent metal, filler wire or electrode. The welding/cutting arc may generate nitrogen oxides, carbon monoxide & other gases, whilst UV radiation emitted from some arcs generates ozone. Ozone may irritate mucous membranes and cause pulmonary oedema & haemorrhage. Shielding gases (e.g. carbon dioxide and inert gases i.e. argon and helium) in high concentrations, in confined spaces, may reduce oxygen in the atmosphere to dangerous levels, resulting in possible asphyxiation.

WELDING (2): In addition to complying with individual exposure standards for specific contaminants, where current manual welding processes are used, the fume concentration inside the welder's helmet should not exceed 5 mg/m³ (unless otherwise classified) when collected in accordance with Australian Standard AS 3853.1: Fume from welding and allied processes - Guide to methods for the sampling and analysis of particulate matter and AS 3853.2: Fume from welding and allied processes - Guide to methods for the sampling and analysis of gases. Airway irritation and metal fume fever are the most common acute effects from welding fumes. Reported to cause reduced sperm quality in welders.

WELDING (3): Other gases and fumes associated with welding processes include: Inert shielding gases (e.g. argon, carbon dioxide, helium) which may reduce the atmospheric oxygen content in poorly ventilated areas. UV-radiation and Infra-Red radiation may decompose chlorinated degreasing agents to form highly toxic and irritating phosgene gas. This may occur if a metal has been degreased but inadequately dried or when vapours from a nearby degreasing bath enter the welding zone.

WELDING (4): Welding fumes may contain a wide variety of chemical contaminants, including oxides and salts of metals and other compounds which may be generated from electrodes, filler wire, flux materials and from the welded material (e.g. painted surfaces). Welding stainless-steel and its alloys generates nickel and chromium (VI) compounds. Welding fumes are retained in the lungs. Sparingly soluble compounds may be released slowly from the lungs. Welding fume is classified as possibly carcinogenic to humans (IARC Group 2B).

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Disclaimer:

We urge each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product.

Harris Products Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for use, handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

WARNING: PRODUCT COMPONENTS PRESENT HEALTH AND SAFETY HAZARDS. READ AND UNDERSTAND THIS SAFETY DATA SHEET (S.DS.). ALSO, FOLLOW YOUR EMPLOYER'S SAFETY PRACTICES.

The information contained herein relates only to the specific product. If the product is combined with other materials, all component properties must be considered. **BE SURE TO CONSULT THE LATEST VERSION OF THE SDS. SAFETY DATA SHEETS ARE AVAILABLE FROM HARRIS PRODUCTS GROUP** Harris Products Group, HGE PTY LTD, Brisbane | Melbourne | Perth | New Zealand, 14 Queensland Rd, Darra, QLD 4076, Phone: (07) 3375 3670 | Fax: (07) 3375 3620, Email: sales@hgea.com.au, www.harrisproductsgroup.com.au,

STATEMENT OF LIABILITY-DISCLAIMER

To the best of the Harris Products Group knowledge, the information and recommendations contained in this publication are reliable and accurate as of the date prepared. However, accuracy, suitability, or completeness are not guaranteed, and no warranty, guarantee, or representation, expressed or implied, is made by Harris Products Group. as to the absolute correctness or sufficiency of any representation contained in this and other publications; Harris Products Group assumes no responsibility in connection therewith; nor can it be assumed that all acceptable safety measures are contained in this and other publications, or that other or additional measures may not be required under particular or exceptional conditions or circumstances. Data may be changed from time to time.

[End of SDS]