

Turn to the **PROS.**



Harris Products Group  
Since 1905

## HARRIS 'C' STYLE TIPS

- ▶ Flame tested for assured consistent quality
- ▶ Manufactured with premium tellurium copper to withstand higher temperatures
- ▶ Reamed and polished bore for exceptional cutting/gouging
- ▶ Chrome jacketed for extended tip life
- ▶ Oxy/Acetylene Type 41

### HERE'S MORE THAN A TIP



*Buy locally for the best service & support.*

Part Number	Description	Oxygen Pressure	Fuel Pressure
CT41-6	Cutting Tip "C" style, type 41, Oxy/Acet, Size 6: 3-6mm	200kpa	100kpa
CT41-8	Cutting Tip "C" style, type 41, Oxy/Acet, Size 8: 6-10mm	200kpa	100kpa
CT41-12	Cutting Tip "C" style, type 41, Oxy/Acet, Size 12: 12-20mm	250kpa	100kpa
CT41-15	Cutting Tip "C" style, type 41, Oxy/Acet, Size 15: 25-75mm	350kpa	100kpa
CT41-20	Cutting Tip "C" style, type 41, Oxy/Acet, Size 20: 100-125mm	400kpa	100kpa
CT41-24	Cutting Tip "C" style, type 41, Oxy/Acet, Size 24: 150-200mm	500kpa	100kpa
CT41-32	Cutting Tip "C" style, type 41, Oxy/Acet, Size 32: 225-300mm	600kpa	100kpa
CT41-32GB	Couging Tip "C" style, type 41, Oxy/Acet, Size 32: Gouging Bent	500kpa	100kpa
CT41-32GS	Couging Tip "C" style, type 41, Oxy/Acet, Size 32: Gouging Straight	500kpa	100kpa
CT41-48GB	Couging Tip "C" style, type 41, Oxy/Acet, Size 48: Gouging Bent	600kpa	100kpa

# HARRIS 'C' STYLE TIPS

Turn to the **PROS.**



- ▶ Flame tested for assured consistent quality
- ▶ Manufactured with premium tellurium copper to withstand higher temperatures
- ▶ Reamed and polished bore for exceptional cutting/gouging
- ▶ Chrome jacketed for extended tip life
- ▶ Oxy/LPG Type 44

## HERE'S MORE THAN A TIP

Part Number	Description	Oxygen Pressure	Fuel Pressure
CT44-6	Cutting Tip "C" style, type 44, Oxy/LPG, Size 6: 3-6mm	200kpa	100kpa
CT44-8	Cutting Tip "C" style, type 44, Oxy/LPG, Size 8: 6-10mm	200kpa	100kpa
CT44-12	Cutting Tip "C" style, type 44, Oxy/LPG, Size 12: 12-20mm	250kpa	100kpa
CT44-15	Cutting Tip "C" style, type 44 Oxy/LPG, Size 15: 25-75mm	350kpa	100kpa
CT44-20	Cutting Tip "C" style, type 44, Oxy/LPG, Size 20: 100-125mm	400kpa	100kpa
CT44-24	Cutting Tip "C" style, type 44, Oxy/LPG, Size 24: 150-200mm	500kpa	100kpa
CT44-32	Cutting Tip "C" style, type 44, Oxy/LPG, Size 32: 225-300mm	600kpa	100kpa
CT44-32GB	Gouging Tip "C" style, type 44, Oxy/LPG, Size 32: Gouging Bent	500kpa	100kpa
CT44-32GS	Gouging Tip "C" style, type 44, Oxy/LPG, Size 32: Gouging Straight	500kpa	100kpa
CT44-48GB	Gouging Tip "C" style, type 44, Oxy/LPG, Size 48: Gouging Bent	600kpa	100kpa



*Buy locally for the best service & support.*

Harris Products Group  
HGE PTY LTD

Brisbane | Melbourne | Perth | New Zealand  
14 Queensland Rd, Darra, QLD 4076  
Phone: (07) 3375 3670 | Fax: (07) 3375 3620

Email: [sales@hgea.com.au](mailto:sales@hgea.com.au)

[www.harrisproductsgroup.com.au](http://www.harrisproductsgroup.com.au)

Email NZ: [sales@harrisnz.com](mailto:sales@harrisnz.com)

[www.harrisproductsgroup.co.nz](http://www.harrisproductsgroup.co.nz)