HARRIS

Cutting Attachments



Follows the design of the professional (493F) cutting attachment specs, and is made to be **compatible** with other brands. The compatible range is easily identified. The tightening sleeve is machined differently to the 493F (refer P29).

Features include- Wt. 0.8kg

- Triangular stainless steel gas tubes for maximum strength and safety
- ▶ Slide 'O' ring sealing makes it compatible
- Accessible injector allows simple change over to other gases.
- Accepts flat seating tips, greatly reducing head popping.
- Built in safety plug in head
- ▶ Universal mixing for maximum economy, fuel gas 1.5kPa
- ▶ Head, lever, body solid brass construction for long life
- Cuts to 150 mm.
- ▶ Ease-on built in for better starts and piercing

1492FHC

* Professional Cutt Att. Propane, LPG, Natural Gas to suit **Harris** "Compatible" Handle and other manufacturers.

AVAILABLE IN POP HANG SELL

733HC

* Professional Cutt Att. Acetylene, to suit Harris

Handle (I432HC). Fits most makes of

Handles."Compatible"

6259B Tip nut

The **733HC** is an expansion of the above Professional range and is considered the toughest in the market:

Features include- Wt. 0.8kg

- ▶ Triangular stainless steel gas tubes
- ▶ Solid brass head
- Accepts standard taper seating tips
- Solid brass body
- ▶ Solid brass lever
- One mixer for all fuel gases
- ▶ Compatible with other manufacturers
- Made in Europe
- ▶ Ease-on built in for better starts and piercing

9005218 Tip nut to suit

Note: Harris type 41 and 44 tips are available refer price list.